

Qty. Description

1 UPA 15-120



Note! Product picture may differ from actual product

Product No.: [99553575](#)

Grundfos UPA 15-120 is a domestic booster designed for pressure boosting of drinking water supplied from an external source in residential homes. The UPA booster pumps increase the pressure of domestic water to make the required pressure available at showers, taps and other tapping points.

This pump has an inlet and outlet port of 1 inch. The pressure rating of the pump corresponds with PN 10 and a port-to-port length of 200 mm.

The UPA 15-120 provides the comfort of constant water pressure with automatic start and stop. This is controlled by the integrated flow switch ensuring optimal start/stop of the booster pump according to demand.

The design is robust and built upon corrosion-free materials and cataphoresis-coated cast iron pump housing to ensure a long lifetime.

The pump is a canned rotor pump type where pump and motor form an integral unit without shaft seal.

This pump must always be installed with horizontal motor shaft.

This booster has a 2-pole, asynchronous, squirrel-cage motor with thermal protection.

The bearings are lubricated by the pumped liquid.

These constructional features ensure maintenance-free operation.

The pump has the following approvals CE,WEEE-UPA,MORO.

- Integrated flow switch: Automatic start and stop according to demand
- Low noise level
- Easy installation: plug and pump compact inline booster
- Integrated non-return valve
- Improved corrosion resistance
- Built in motor protection

Controls:

Flow switch (Yes/No): Y

Liquid:

Pumped liquid: Water

Liquid temperature range: 2 .. 95 °C

Selected liquid temperature: 60 °C

Density: 983.2 kg/m³

Technical:

Rated flow: 1.33 m³/h

Rated head: 8.138 m

TF class: 95

Approvals: CE,WEEE-UPA,MORO

Materials:

Pump housing: Cast iron
EN 1561 EN-GJL-150

Impeller: Composite



Company name:

Created by:

Phone:

Date:

28/05/2024

Qty. Description

1	PP-GF30
Installation:	
Range of ambient temperature:	0 .. 40 °C
Maximum operating pressure:	10 bar
Type of connection:	G
Size of connection:	1 inch
Pressure rating for connection:	PN 10
Port-to-port length:	200 mm
Electrical data:	
Max. power input:	200 W
Mains frequency:	50 Hz
Rated voltage:	1 x 230 V
Maximum current consumption:	0.89 A
Capacitor size - run:	6 µF
Enclosure class (IEC 34-5):	X2D
Insulation class (IEC 85):	F
Built-in motor protection:	CONTACT
Power plug:	Schuko plug
Others:	
Net weight:	4.79 kg
Gross weight:	5.45 kg
Shipping volume:	0.006 m ³
Country of origin:	CN
Custom tariff no.:	84137030